

D	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF: LOCATION								
	LARGE GENERAL PURPOSE ROOF DRAIN								
	LOW PROFILE DOME WITH EXTENSION AND SECONDARY FLASHING CLAMP								
	Free Area 102.5 Sq. In. (661) Sq. Cm. 5 1/4 (135) Extension (-E) (Specify Height) Δ3 3/4 (95) ΔΔ5 (125) Δ This Dimension to Internal Stop of Speedi-Set® Gasket ΔΔ Same for Caulk, No Hub and Speedi-Set®. 3 3/4 (95) for Threaded. 15 1/4(390) Dia. 11(280) Dia. A Polyethylene Dome Combined Flashing and Gravel Stop Extension (-E) Seepage Openings 2 Rows of 1/4" Holes Secondary Flashing Clamp (-C2) Waterproofing 1 1/8(29) Min. Underdeck Clamp (When Specified) <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">recommended deck opening</td> </tr> <tr> <td style="padding: 2px;">with suffix -R</td> <td style="padding: 2px;">17 (430) DIA</td> </tr> <tr> <td style="padding: 2px;">less suffix -R</td> <td style="padding: 2px;">14 (355) DIA</td> </tr> </table>				recommended deck opening		with suffix -R	17 (430) DIA	less suffix -R
recommended deck opening									
with suffix -R	17 (430) DIA								
less suffix -R	14 (355) DIA								
REGULARLY FURNISHED: Duco Cast Iron Body with Combined Flashing Clamp and Gravel Stop, Cast Iron Extension with 2 Rows of Seepage Openings, Secondary Flashing Clamp and Polyethylene Dome. VARIATIONS: ☐ Expansion Joint (Specify Fig. 1710) ☐ "L" Shaped Underdeck Clamp - CL ☐ L Speedi-Set® Service Weight 02(50), 03(75) & 04(100) sizes ☐ LXH Speedi-Set® Extra Heavy 02(50), 03(75), & 04(100) sizes ☐ Sump Receiver -R ☐ Underdeck Clamp -C ☐ Vandal Proof Dome -U ☐ Roof Deck Plate -RDP OPTIONAL MATERIALS: ☐ Aluminum Dome -AD ☐ Galvanized Cast Iron Body and Collar -G ☐ Galvanized Cast Iron Dome -CIDG ☐ Rough Bronze Dome -RBD									